

(2017/01/23) (改7)

## FTD REFERENCER PITCH/PWR (B58)

### PROP FULL FORWARD

実施科目	V1/Vr	V2	Gear	Flaps	PITCH	PWR
TAKE OFF	85kt	100kt	Down	0	+10°	MAX

### PROP 2500rpm

実施科目	ALT	A/S	Gear	Flap	PITCH	PWR
CLIMB		120kt	Up	Up	+8°	25.0 inch.hg
CRUISE	Level	150kt	Up	Up	+0.5°	17.0 inch.hg
DESCENT	500ft/min	150kt	Up	Up	-0.5°	15.0 inch.hg
DESCENT	1000ft/min	150kt	Up	Up	-2°	12.5 inch hg
HOLDING	Level	120kt	Up	Up	+3°	15.0 inch.hg
DESCENT	500ft/min	120kt	Up	Up	0°	12.0 inch hg
APPROACH	Level	105kt	Up	F-App	2°	15.5 inch.hg

### PROP FULL FORWARD

実施科目	ALT	A/S	Gear	Flap	PITCH	PWR
APPROACH	Level	105kt	Down	App	+2.5°	17.5 inch hg
ILS APCH	1000ft 以上	105kt	Down	App	-0.5°	14.5 inch.hg
ON G/S	1000ft以下	105kt	Down	LDG	-1.0°	15.0 inch.hg

Take off: Positive Climb...Gear Up

400ft...Set Climb PWR (2500 rpm 25 inch.hg)

ILS App :3nm before G/S ...Flap App-Prop Full Forward

1 Dot before G/S...Gear Down

1000ft...Flap LDG

VOR App: Base turn inbound...Flap App/ Gear down/Prop full forward

RWY in sight and LDG Assure...Flap LDG

※無断転用禁止